



## **Electrical:**

Impedance: 50 ohm

Frequency Range: 0~4 GHz.

Voltage Rating :  $\ge 500 \text{ V rms}$  (depending on cable)

Insulator Resistance :  $\geq 5 \text{ G}\Omega$ 

Dielectric Withstanding Voltage: 1500 V rms. Contact Resistance : Center Contact  $\leq 1.5 \text{ m}\Omega$ .

Outer Contact  $\leq 1 \text{ m}\Omega$ .

Cable Type	Dimensions					
	Α	В	С	D		
RG174,316	1.7	2.7	0.6	3.2		
RG316 Double Braided	1.7	2.7	0.6	3.6		
RG58	3.1	4.5	1.0	5.6		
RG142,400	3.1	4.6	1.0	5.6		
RG8,213	7.5	9.5	2.4	11.3		
RG214	7.6	9.6	2.9	10.9		
LMR200	3.2	4.6	1.2	5.8		
LMR400	7.5	9.5	2.8	10.7		
5D-2V	5.1	6.5	1.9	8.5		

## **Mechanical:**

Mating: Bayonet Coupling.

Recommended Mating Torque: 0.6~2.5 lbs Coupling Nut Retention Force :  $\geq 101.2$  lbs

## **Environmental:**

Temperature Range: -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101,

Cond. C

Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. G Vibration: MIL-STD-202, Method 204, Cond. B

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- A complete information for connectors is available upon request.

Scale	Abbr.		Date		Rev.	
NTS	ST		2019/06/04		В	
Tolerances : .X ±0.2		$\oplus$				
.XX ±0		All Dimensions in mm (Unless Otherwise Specified)				
Drawn		Checked		Approved		
Mark		Ryan		G	. Sun	
2019/06/0	14	2019/0	06/04	201	19/06/04	

Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclosed

or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan

Customer P/N: Nil

DWG.NO.

B101-50



TITLE

BNC S/T Plug, Crimp Type (50 $\Omega$ )



