



Dimensions

Type	Α	В	С	D		
RG174,316	2.7	3.7	0.7	4.6		
RG316 Double Braided	2.5	4.0	0.6	4.5		
RG179(75Ω)	1.7	2.7	0.5	3.2		
RG58	3.9	5.5	0.7	6.6		
2.5C-2V(75Ω)	2.5	3.8	0.5	4.5		
ΒΤ3002(75Ω)	2.1	3.2	0.5	4.2		

3.6

0.5

3.7

Cable

735A(75Ω)

Electrical:

Impedance: 50/75 ohm

Frequency Range: 0~4 / 0~1GHz.

Voltage Rating: 250 V rms.(depending on cable)

Insulator Resistance : $\geq 1 \text{ G}\Omega$

Dielectric Withstanding Voltage: 750 V rms. Contact Resistance : Center Contact $\leq 10 \text{ m}\Omega$. Outer Contact $\leq 3 \text{ m}\Omega$.

Mechanical:

Mating: Bayonet Coupling. Engagement Force : ≤ 2.3 lbs Disengagement Force : ≤ 2.3 lbs

Environmental:

Temperature Range: -40°C to 85°C

Corrosion (Salt Spray): MIL-STD-202, Method 101,

Cond. C

Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. B

Vibration: MIL-STD-202, Method 204, Cond. A

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- A complete information for connectors is available upon request.

Scale	Abbr.		Date		Rev.	
NTS	i	ST	2019/06/04		В	
Tolerances .X ±0	ss: ±0.2					
.XX ±0		All Dimensions in mm (Unless Otherwise Specified)				
Drawn		Checked		Approved		
Mark		Ryan		G.	Sun	
2019/06/0	14	2019/0	06/04	201	19/06/04	

DWG.NO. This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or

Proprietary Note

This document or parts thereof, may not be used, disclosed

or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan

protected by trade secret laws.

Customer P/N: Nil

B101



TITLE

1.0/2.3 S/T Plug, Crimp Type

S-Conn Enterprise Co., Ltd.

