

Mechanical:

Mating: Bayonet Coupling.

Recommended Mating Torque : $0.6\sim2.5$ lbs Coupling Nut Retention Force : ≥ 101.2 lbs

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

Scale	A	.bbr.	Dat	e	Rev.
NTS	ST		2019/07/02		В
Tolerances : .X ±0.2		$\oplus \Box$			
.XX ±0.1 .XXX ±0.05		All Dimensions in mm (Unless Otherwise Specified)			
Drawn		Checked		Approved	
Mark 2019/07/02		Ryan 2019/07/02		G. Sun 2019/07/02	

Proprietary Note
This document contains information proprietary to S-Conn,
which is either copyrighted, or patent applied for, and / or
protected by trade secret laws.
This document or parts thereof, may not be used, disclosed

This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.

Customer P/N: Nil

DWG.NO.

B109



TITLE

Protective Cap for BNC Jack



