

| | Туре | Dimensions | | | | | | | | | | | |
|----|------|------------|------|-----|------|-----|------|-----|-----|------|--|--|--|
| | | A | В | С | D | E | F | а | b | d | | | |
| | F0 | 0.9 | 0.9 | 8.1 | 9.8 | 4.6 | 23.4 | 1.3 | 1.5 | 6.35 | | | |
| | F1 | 0.95 | 0.85 | 8.1 | 9.8 | 4.6 | 23.4 | 1.3 | 1.5 | 6.35 | | | |
| | F2 | 0.9 | 0.9 | 8.1 | 9.85 | 4.6 | 23.4 | 1.3 | 1.5 | 6.36 | | | |
| | F9 | 0.95 | 0.9 | 8.1 | 9.85 | 4.5 | 18.2 | 1.3 | 1.5 | 6.35 | | | |
| | A0 | 0.95 | 0.85 | 8.1 | 9.8 | 4.5 | 18.2 | 1.3 | 1.5 | 6.35 | | | |
| e) | A1 | 1 | 0.9 | 8.1 | 9.85 | 4.5 | 23.3 | 1.3 | 1.5 | 6.36 | | | |

Electrical:

Impedance: 50 / 75 ohm

Voltage Rating : ≥500 V rms (depending on cable)

Insulator Resistance : $\geq 5 \text{ G}\Omega$

Dielectric Withstanding Voltage : 1500 V rms . Contact Resistance : Center Contact \leq 1.5 m Ω . Outer Contact \leq 1 m Ω .

Mechanical:

Mating: Bayonet Coupling.

Recommended Mating Torque : $0.6\sim2.5$ lbs Coupling Nut Retention Force : ≥ 101.2 lbs

Environmental:

Temperature Range: -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101,

Cond. C

Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. G Vibration: MIL-STD-202, Method 204, Cond. B

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

B230

| Scale A | | bbr. | Date | | Rev. | Proprietary Note This document contains information proprietary to S-Comwhich is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclose | | | | |
|-----------------|----|--|------------|----|---------|--|--|--|--|--|
| NTS | ST | | 2019/07/05 | | В | | | | | |
| Tolerances : .X | | $\oplus \Box$ | | | | or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiw | | | | |
| | | All Dimensions in mm (Unless Otherwise Specified) | | | | Customer P/N: Nil | | | | |
| | | Chec | cked A | | proved | | | | | |
| | | Ryan G 2019/07/05 20 | | G. | Sun | S-Conn En | | | | |
| 2019 07 0 | 25 | 2019/0 | 7/05 201 | | 9107105 | | | | | |

TITLE
BNC S/T Jack, PCB Mount Type



S-Conn Enterprise Co., Ltd.

DWG.NO.