

Electrical:

Impedance: 75 ohm

Voltage Rating: 250 V rms. (depending on cable)

Insulator Resistance : $\ge 1 \text{ G}\Omega$

Dielectric Withstanding Voltage : 750 V rms . Contact Resistance : Center Contact \leq 10 m Ω . Outer Contact \leq 3 m Ω .

Mechanical:

Mating : Quick-Lock Coupling. Engagement Force : ≤ 2.3 lbs Disengagement Force : ≤ 2.3 lbs

	Cable Type	Dimensions					
		Α	В	С	D		
	1855A(75Ω)	2.7	3.7	0.7	4.6		
	1865A(75Ω)	2.5	4.0	0.6	4.5		
	RG179(75Ω)	1.7	2.7	0.5	3.2		
	RG59(75Ω)	3.9	5.5	0.7	6.6		
	2.5C-2V(75Ω)	2.5	3.8	0.5	4.5		
	BT3002(75Ω)	2.1	3.2	0.5	4.2		
	735Α(75Ω)	2.4	3.6	0.5	3.7		

Environmental:

Temperature Range: -40°C to 85°C

Corrosion (Salt Spray): MIL-STD-202, Method 101,

Cond. B

Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. B Vibration: MIL-STD-202, Method 204, Cond. A

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

L	Scale	A	bbr.	Dat	e	Rev.	
I	NTS	,	ST	2019/06/19		В	
	Tolerances .X ±0	:).2	$\oplus \Box$				
	.XX ±0		All Dimensions in mm (Unless Otherwise Specified)				
I	Drawn		Checked		Approved		
1	Mark 2019/06/19		Ryan 2019/06/19		G. Sun 2019/06/19		

Proprietary Note
This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.
This document or parts thereof, may not be used, disclosed

This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.

Customer P/N: Nil

DWG.NO.

C101



TITLE

1.0/2.3 S/T Plug, Crimp Type

S-Conn Enterprise Co., Ltd.

