

## Electrical :

Impedance : 50 ohm

Voltage Rating :  $\geq 335$  V rms. (depending on cable)

Insulator Resistance :  $\geq 1$  G $\Omega$

Dielectric Withstanding Voltage : 750 V rms.

Contact Resistance : Center Contact  $\leq 5$  m $\Omega$ .

Outer Contact  $\leq 2.5$  m $\Omega$ .

## Mechanical :

Mating : Sanp-on Coupling

Engagement Force :  $\leq 3.4$  lbs

Disengagement Force : 1.4 lbs ~ 3.4 lbs

## Environmental :

Corrosion (Salt Spray) : MIL-STD-202, Method 101, Cond. B

Thermal Shock : MIL-STD-202, Method 107, Cond. F





Mechanical : MIL-STD-202, Method 213, Cond. B

Vibration : MIL-STD-202, Method 204, Cond. C

Type	Dimensions						
	A	B	C	D	a	b	c
A0	0.94	0.8	5.08	6.35	1.1	1.5	5.08

## Notes :

1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
2. Any changes for interface dimensions are strictly prohibited.
3. The Material and plating are in various options per customer's request.
4. A complete information for connectors is available upon request.

Scale	Abbr.	Date	Rev.	<div>Proprietary Note</div> <div>This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.</div> <div>This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.</div>	DWG.NO.	<div>MX105</div> <div></div>
NTS	ST	2019/07/11	B		TITLE	
<div>Tolerances : .X ±0.2 .XX ±0.1 .XXX ±0.05</div> <div><div>All Dimensions in mm (Unless Otherwise Specified)</div></div>					MCX S/T Plug, PCB Mount Type	
Drawn	Checked	Approved		Customer P/N: Nil	<div></div> <div><i>S-Conn Enterprise Co., Ltd.</i></div> <div></div>	
Mark	Ryan	G. Sun				
2019/07/11	2019/07/11	2019/07/11				