



Recommended PCB Layout

Electrical :

Impedance : 50 ohm
 Voltage Rating : ≥ 335 V rms. (depending on cable)
 Insulator Resistance : ≥ 1 G Ω
 Dielectric Withstanding Voltage : 750 V rms.
 Contact Resistance : Center Contact ≤ 5 m Ω .
 Outer Contact ≤ 2.5 m Ω .

Type	Dimensions						
	A	B	C	D	a	b	c
A0	0.5	0.8	5.08	4	0.8	1.4	5.08
A1	0.95	0.8	5.08	4	1.2	1.4	5.08
N0	0.95	0.8	5.08	3	1.2	1.4	5.08

Mechanical :

Mating : Sanp-on Coupling
 Engagement Force : ≤ 3.4 lbs
 Disengagement Force : 1.4 lbs ~ 3.4 lbs

Environmental :

Corrosion (Salt Spray) : MIL-STD-202, Method 101, Cond. B
 Thermal Shock : MIL-STD-202, Method 107, Cond. F
 Mechanical : MIL-STD-202, Method 213, Cond. B
 Vibration : MIL-STD-202, Method 204, Cond. C

Notes :

1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
2. Any changes for interface dimensions are strictly prohibited.
3. The Material and plating are in various options per customer's request.
4. A complete information for connectors is available upon request.

Scale	Abbr.	Date	Rev.	Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. Customer P/N: Nil	DWG.NO.	MX208 MCX R/A Jack, PCB Mount Type		
NTS	ST	2019/07/12	B		TITLE			
Tolerances : .X ± 0.2 .XX ± 0.1 .XXX ± 0.05				All Dimensions in mm (Unless Otherwise Specified)	Drawn: Mark Checked: Ryan Approved: G. Sun			
Mark 2019/07/12					Ryan 2019/07/12			G. Sun 2019/07/12