

Cable Type	Dimensions			
	A	В	С	
3D-2V	1.0	4.0	6.0	
5D-2V	1.6	5.6	8.0	
8D-2V	3.1	10.4	12	
10D-2V	3.1	12.7	14	

Electrical:

Impedance: 50 ohm

Voltage Rating : $\ge 1000 \text{ V rms}$ (depending on cable)

Insulator Resistance : $\ge 5 \text{ G}\Omega$

Dielectric Withstanding Voltage: 2500 V rms. Contact Resistance : Center Contact $\leq 1 \text{ m}\Omega$. Outer Contact $\leq 1 \text{ m}\Omega$.

Mechanical:

Mating: 5/8-24 UNEF Screw-on.

Recommended Mating Torque: 6.0~10.0 lbs Coupling Nut Retention Force : ≥ 101.3 lbs

Environmental:

Temperature Range: -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101, Cond. C

Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. I Vibration: MIL-STD-202, Method 204, Cond. B

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

		oate 9/07/09	Rev.	Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.	DWG.NO. N106
Tolerances: .X ±0.2 .XX ±0.1 .XXX ±0.05		ensions in	n mm	This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. Customer P/N: Nil	TITLE N S/T Plug, Clamp Type
Drawn <i>Wark</i> 2017/03/16	Checked Ryan 2017/03/16	G.	proved Sun 7/03/16	S-Conn Ent	erprise Co., Ltd.



