

### Notes :





1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
2. Any changes for interface dimensions are strictly prohibited.
3. The Material and plating are in various options per customer's request.
4. A complete information for connectors is available upon request.

### Mechanical :

Mating : 5/8-24 UNEF Screw-on.

Recommended Mating Torque : 6.0~10.0 lbs

Coupling Nut Retention Force :  $\geq 101.3$  lbs

Scale	Abbr.	Date	Rev.	<div>Proprietary Note</div> <div>This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.</div> <div>This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.</div>	DWG.NO.	<div>N233</div> <div></div>
NTS	ST	2019/07/12	B		TITLE	
Tolerances : .X ±0.2 .XX ±0.1 .XXX ±0.05		<div></div> <div>All Dimensions in mm (Unless Otherwise Specified)</div>		Customer P/N: Nil	Protective Cap for N Plug	
Drawn	Checked	Approved		<div><div>S-Conn Enterprise Co., Ltd.</div><div> let's Connect The World!</div></div>		
Mark	Ryan	G. Sun				
2017/03/16	2017/03/16	2017/03/16				