



Recommend PCB Layout

Electrical:

Impedance: 50 ohm

Voltage Rating : \geq 500 V rms MIN. (depending on cable)

Insulator Resistance : $\geqq 5~\text{G}\Omega$

Dielectric Withstanding Voltage: 1000 V rms. Contact Resistance : Center Contact $\leq 3 \text{ m}\Omega$. Outer Contact \leq 2.5 m Ω .

| _ | Dimensions | | | | | | | | |
|------|------------|------|-----|------|------|------|------|--|--|
| Туре | A | В | C | D | а | b | d | | |
| LO | 1.27 | 1.02 | 7.0 | 5.08 | 1.50 | 1.70 | 5.08 | | |

Mechanical:

Mating: 1/4-36 UNS Screw-on Coupling. Recommended Mating Torque: 7.1~9.7 lbs Coupling Nut Retention Force : \ge 60.7 lbs

Environmental:

Temperature Range : -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101, Cond. B Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. I Vibration: MIL-STD-202, Method 204, Cond. D

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.

S205

4. A complete information for connectors is available upon request.

| Scale | Abbr. | Date | Rev. | Proprietary Note This document contains information proprietary to S-Conn, | | |
|-------------------|------------|------------------------------|------------|--|--|--|
| NTS ST | | 2019/07/02 | В | which is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclosed | | |
| Tolerances .X ±0 | :).2 | ⊕ ∈ | | or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. | | |
| | | ll Dimension ss Otherwise | | Customer P/N: Nil | | |
| Drawn | Che | cked A | Approved | | | |
| Mark 2019 07 0 | Ry. 201910 | an G | . Sun | S-Conn Ent | | |
| 2019/07/0 | 2019/0 | 11/02 20 | 20/10/10/1 | | | |

SMA S/T Jack, PCB Mount Type



DWG.NO.

TITLE

