



## **Electrical:**

Impedance: 50 ohm

Voltage Rating : ≥500 V rms MIN. (depending on cable)

Insulator Resistance :  $\geqq 5 \text{ G}\Omega$ 

Dielectric Withstanding Voltage: 1000 V rms. Contact Resistance : Center Contact  $\leq 3 \text{ m}\Omega$ . Outer Contact  $\leq 2.5 \text{ m}\Omega$ .

## **Mechanical:**

Mating: 1/4-36 UNS Screw-on Coupling. Recommended Mating Torque: 7.1~9.7 lbs Coupling Nut Retention Force :  $\ge 60.7$  lbs

## **Environmental:**

Temperature Range: -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101, Cond. B Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. I Vibration: MIL-STD-202, Method 204, Cond. D

| _    | Dimensions |       |     |      |   |  |
|------|------------|-------|-----|------|---|--|
| Туре | A          | A B C |     | D    | E |  |
| L1   | 1.27       | 5.0   | 2.6 | 12.2 | 6 |  |
| L2   | 1.27       | 6.0   | 2.6 | 12.2 | 6 |  |
| L3   | 1.27       | 8.0   | 2.6 | 12.2 | 6 |  |
| L4   | 1.27       | 10.0  | 2.6 | 12.2 | 6 |  |
| L5   | 1.27       | 15.0  | 2.6 | 12.2 | 6 |  |

## **Notes:**

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

| bbr.   | Date                           | Rev.  | Proprietary Note This document contains information proprietary to S-Conn,                                     | DWG.NO.  | G221   |
|--|--------------------------------|---|--|--|--|
| ST 20  | 019/07/03                      | В   | protected by trade secret laws.  |  | S221   |
| (  | <b>⊕</b> ∈                     | <del>]</del>  | or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. | TITLE  | SMA P/M 2-Hole J   |
| .XX $\pm 0.1$ All Dimensions in mm<br>.XXX $\pm 0.05$ (Unless Otherwise Specified) |                                |   | Customer P/N: Nil  |  | Receptacle (Extended   |
| Checke   | ed A                           | pproved   |  |  |  |
| Mark Ryan G. Sun 2017/03/17 2017/03/17 2017/03/17                                  |                                |   | S-Conn Enterprise Co., Ltd   |  |  |
|  | ST 2  All D  (Unless 0  Checke | ST 2019/07/03  All Dimensions (Unless Otherwise Steeked A)  Ryan G. | ST 2019/07/03 B  All Dimensions in mm (Unless Otherwise Specified)  Checked Approved  Ryan G. Sun              | This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.  Customer P/N: Nil  Checked Approved  Ryan G. Sun S-CONN Ent | This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  Title  TITLE  TITLE  TITLE  TITLE  S-Conn Enterpri |



Jack, d PTFE)

