

Electrical:

Impedance: 50 ohm

Voltage Rating: 250 V rms MIN. (depending on cable)

Insulator Resistance : $\ge 1 \text{ G}\Omega$

Dielectric Withstanding Voltage : 750 V rms . Contact Resistance : Center Contact \leq 5 m Ω .

Outer Contact $\leq 2.5 \text{ m}\Omega$

Mechanical:

Mating : Snap-on Coupling. Engagement Force : ≤ 14.2 lbs Disengagement Force : $1.8\sim14.2$ lbs

Cable	Dimensions			
Type	A	В	C	
RG174,316	1.7	2.3	3.0	
RG179(75Ω)	1.7	2.3	3.0	
RG58	3.1	4.5	5.4	
LMR 200	3.1	4.5	5.6	
ΒΤ3002(75Ω)	2.1	3.2	4.2	
735Α(75Ω)	2.4	3.6	3.7	

Environmental:

Temperature Range : -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101,

Cond. B

Thermal Shock : MIL-STD-202, Method 107, Cond. B Mechanical : MIL-STD-202, Method 213, Cond. B

Vibration: MIL-STD-202, Method 204, Cond. D

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

Scale	Abbr.		Date		Rev.	
NTS		ST	2019/07/19		В	
$ \begin{array}{ll} \text{Tolerances}: \\ .X & \pm 0.2 \\ .XX & \pm 0.1 \\ .XXX & \pm 0.05 \end{array} $		⊕ ⊟				
		All Dimensions in mm (Unless Otherwise Specified)				
Drawn		Checked		Approved		
Mark		Ryan		G.	Sun	
2019 07 1	9	2019/0	7/19	201	9 07 19	

Proprietary Note
This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.

This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.

purpose, without the written permission of S-Conn, Ta

Customer P/N: Nil

DWG.NO.

SB103



TITLE

SMB R/A Plug, Crimp Type

S-Conn Enterprise Co., Ltd.

