



## **Electrical:**

Impedance: 50 ohm

Voltage Rating: 250 V rms MIN. (depending on cable)

Insulator Resistance :  $\ge 1 \text{ G}\Omega$ 

Dielectric Withstanding Voltage: 750 V rms. Contact Resistance : Center Contact  $\leq 5 \text{ m}\Omega$ .

Outer Contact  $\leq 2.5 \text{ m}\Omega$ 

Туре	Dimensions						
	A	В	C	D	Е		
L0	0.51	1.65	3.94	6.35	1.02		

## **Mechanical:**

Mating: Snap-on Coupling. Engagement Force :  $\leq 14.2 \text{ lbs}$ Disengagement Force: 1.8~14.2 lbs

## **Environmental:**

Temperature Range: -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101,

Cond. B

Thermal Shock: MIL-STD-202, Method 107, Cond. B

Mechanical: MIL-STD-202, Method 213, Cond. B Vibration: MIL-STD-202, Method 204, Cond. D

## Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

Scale	Scale A		Date		Rev.		
NTS	ST		2019/07/23		В		
Tolerances : .X ±0.2		$\oplus \Box$					
.XX ±0.1 .XXX ±0.05		All Dimensions in mm (Unless Otherwise Specified)					
Drawn		Chec	ked	Approved			
Mark		Ryan		G.	Sun		
2017 03 17		2017/0	13/17	201	17 03 17		

Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.

This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.

Customer P/N: Nil

**SB233** 



TITLE

DWG.NO.

SMB S/T Jack, End Launch Type

S-Conn Enterprise Co., Ltd.

