





Specification :

Insertion Loss :	0.5 dBi Max
Impedence :	50 Ω
Gas Tube DC :	230V \pm 20 %
Gas Tube Impulse Breakdown Voltage :	\leq 700V
Gas Tube Insulation Resistance :	\geq 10000 MΩ
Max Withstand Current :	20 A
RF Power Rating :	15 W
Operating Temperature :	-40°C ~ +85°C

Notes :

1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
2. Any changes for interface dimensions are strictly prohibited.
3. The Material and plating are in various options per customer's request.
4. A complete information for connectors is available upon request.

Scale	Abbr.	Date	Rev.	<p>Proprietary Note</p> <p>This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.</p> <p>This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.</p>	DWG.NO.	SG05		
NTS	ST	2019/07/19	B					
Tolerances :		 	<p>TITLE</p> <p>N B/H Jack to N Jack, Surge Protector</p>					
.X	±0.2							
.XX	±0.1							
.XXX	±0.05							
		All Dimensions in mm (Unless Otherwise Specified)	Customer P/N: Nil					
Drawn	Checked	Approved	<p><i>S-Conn Enterprise Co., Ltd.</i></p>					 <i>Let's Connect The World!</i>
Mark	Ryan	G. Sun						
2019/07/19	2019/07/19	2019/07/19						