



Specification :

Insertion Loss :	0.5 dBi Max
Impedence :	50 Ω
Gas Tube DC :	230V \pm 20 %
Gas Tube Impulse Breakdown Voltage :	\leq 700V
Gas Tube Insulation Resistance :	\geq 10000 MΩ
Max Withstand Current :	20 A
RF Power Rating :	15 W
Operating Temperature :	-40°C ~ +85°C

Notes :

1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
2. Any changes for interface dimensions are strictly prohibited.
3. The Material and plating are in various options per customer's request.
4. A complete information for connectors is available upon request.

Scale	Abbr.	Date	Rev.
NTS	ST	2019/07/22	B

Tolerances :	
.X \pm 0.2	
.XX \pm 0.1	
.XXX \pm 0.05	

All Dimensions in mm
(Unless Otherwise Specified)

Proprietary Note
This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.

This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.

Customer P/N: Nil

DWG.NO.

SG08



TITLE

SMA Plug to Plug , Surge Protector

Drawn	Checked	Approved
Mark	Ryan	G. Sun
2019/07/22	2019/07/22	2019/07/22

S-Conn Enterprise Co., Ltd.

