



## Specification :

Insertion Loss :	<b>0.9 dBi Max</b>
Impedence :	<b>50 Ω</b>
Gas Tube DC :	<b>230V ± 20 %</b>
Gas Tube Impulse Breakdown Voltage :	<b>≤ 700V</b>
Gas Tube Insulation Resistance :	<b>≥ 10000 MΩ</b>
Max Withstand Current :	<b>20 A</b>
RF Power Rating :	<b>15 W</b>
Operating Temperature :	<b>-40°C ~ +85°C</b>

## Notes :

1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
2. Any changes for interface dimensions are strictly prohibited.
3. The Material and plating are in various options per customer's request.
4. A complete information for connectors is available upon request.

Scale	Abbr.	Date	Rev.
NTS	ST	2019/07/22	B

Tolerances :	
.X ±0.2	
.XX ±0.1	
.XXX ±0.05	
All Dimensions in mm (Unless Otherwise Specified)	

Drawn	Checked	Approved
Mark	Ryan	G. Sun
2019/07/22	2019/07/22	2019/07/22

**Proprietary Note**  
This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws.  
This document or parts thereof, may not be used, disclosed or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan.

Customer P/N: Nil

DWG.NO.

SG10

TITLE

UHF Jack to Plug , Surge Protector



**S-Conn Enterprise Co., Ltd.**

