



Recommended PCB Layout

Cable Type	Dimensions								
	Α	В	С	D	Е	а	d		
RG174,316	0.65	3.1	0.5	2.54	4	0.8	2.54		

Electrical:

Impedance: 50 ohm

Voltage Rating: 250 V rms MIN. (depending on cable)

Insulator Resistance : $\geq 1 \text{ G}\Omega$

Dielectric Withstanding Voltage: 750 V rms. Contact Resistance : Center Contact $\leq 5 \text{ m}\Omega$. Outer Contact $\leq 2.5 \text{ m}\Omega$

Mechanical:

Mating: Snap-on Coupling. Engagement Force : ≤ 6 lbs Disengagement Force : ≥ 1.8 lbs

Environmental:

Temperature Range: -65°C to 165°C

Corrosion (Salt Spray): MIL-STD-202, Method 101, Cond. B

Thermal Shock: MIL-STD-202, Method 107, Cond. B Mechanical: MIL-STD-202, Method 213, Cond. B Vibration: MIL-STD-202, Method 204, Cond. D

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

SM204

Scale	Abbr.		Date		Rev.		
NTS	NTS		2019/07/24		В		
Tolerances : .X ±0.2		⊕ ⊟					
.XX ±0		All Dimensions in mm (Unless Otherwise Specified)					
Drawn		Chec	ked	Approved			
Mark 2019/07/24		Ry 0		G.Sun 2019/07/24			

Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws This document or parts thereof, may not be used, disclosed

or reproduced in any form by any method, or for any

Customer P/N: Nil

purpose, without the written permission of S-Conn, Taiwan.

TITLE

DWG.NO.

SSMB S/T Jack, PCB Mount Type



