

Electrical:

Impedance: 50 ohm

Voltage Rating : ≥500 V rms. (depending on cable)

Insulator Resistance : \geq 5 G Ω

Dielectric Withstanding Voltage : 1500 V rms . Contact Resistance : Center Contact \leq 1.5 m Ω . Outer Contact \leq 1 m Ω .

Mechanical:

Mating : 7/16-28 UNEF Screw-on Coupling. Recommended Mating Torque : $4.1\sim6.1$ lbs Coupling Nut Retention Force : ≥101.2 lbs

Environmental:

Temperature Range : -65°C to 165°C Corrosion (Salt Spray) : MIL-STD-202,

Method 101, Cond. B

Thermal Shock: MIL-STD-202, Method 107, Cond. C Mechanical: MIL-STD-202, Method 213, Cond. G Vibration: MIL-STD-202, Method 204, Cond. B

Cable	Dimensions				
Type	A	В	С	D	
RG174,316	1.7	2.7	0.6	3.2	
RG58	3.1	4.5	1.0	5.6	
RG316 Double Braided	1.7	2.7	0.6	3.6	
LMR400	7.4	9.4	2.9	10.9	
RG178	1.7	2.7	0.6	2.1	
1.37	1.5	2.7	0.6		
1.13	0.75	2.0		1.25	
0.81	0.9	3.0		1.0	

Notes:

- 1. The overall contour may be slightly changed per terminating with different cable and we reserve right to change it without notice.
- 2. Any changes for interface dimensions are strictly prohibited.
- 3. The Material and plating are in various options per customer's request.
- 4. A complete information for connectors is available upon request.

Scale NTS	Abbr.	Date 2019/07/16	Rev.	Proprietary Note This document contains information proprietary to S-Conn, which is either copyrighted, or patent applied for, and / or protected by trade secret laws. This document or parts thereof, may not be used, disclosed	DWG.NO.	RoHS 2
		s in mm	or reproduced in any form by any method, or for any purpose, without the written permission of S-Conn, Taiwan. Customer P/N: Nil	TITLE TNC B/H-O Jack, Crimp Type		
Drawn <i>Wark</i> 2019/07/16	Ry	an G	Approved A. Suu 019/07/16	S-Conn Ent	erprise Co., Ltd.	S-GONN ®